

product information

C SERIES C37 / C50

ICE CUBE MAKERS

C SERIES SELF CONTAINED ICE CUBE MAKER

Entirely made of stainless steel, the C Series solid ice cube makers from Kastel are a premium product and incorporate all the latest technology to ensure the highest efficiency and a long service life.

The ice is produced by spraying water on a horizontally mounted copper evaporator which freezes and forms high density, crystal clear ice cubes.

Purer than the water from which they are made, solid crystal clear cubes are the best option for all those situations where we need to keep drinks cool for a long period of time without watering them down.

UNDERCOUNTER: This range of medium sized ice machines can be installed under most counters under 900mm high. They have larger production capabilities than other equivalent machines and are suitable for restaurants, cafes, bars and domestic applications.

These machines are also available with electronic boards or mechanical timers. Both models are for 'tropical use' where they can produce ice even at room temperatures of 43°C and water temperature of 35°C.

Features

- Full stainless steel shell and door
- Available in electronic or mechanical
- Technical support available
- Spare parts for most makes and models





18gm full crystal clear hard ice cube



Manufactured in Italy



Energy efficient



Stainless steel body and door








product information

C SERIES C37 / C50

ICE CUBE MAKERS







| | C37 | C50 | |
|----------------------------|-----------------------|-----------------------|--|
| Control System | C37A C37A-M | C50A C50A-M | |
| Cooling System | Air / Water Cooled | Air / Water Cooled | |
| Ice Production in 24 Hours | 37kg Up to 2176 cubes | 50kg Up to 2941 cubes | |
| Ice Production per cycle | 40 cubes | 40 cubes | |
| Storage Capacity | 15kg | 25kg | |
| Voltage Standard | 220-240V - 50Hz | 220-240V - 50Hz | |
| Power Consumption | 550W | 800W | |
| Type of Refrigerant | R 404 A | R 404 A | |
| Dimensions (W x D x H) | 500 x 585 x 685mm | 500 x 585 x 795mm | |
| Legs* | + 80-150mm | + 80-150mm | |
| Net Weight | 52kg | 55kg | |
| Packing Dimensions | 580 x 650 x 830mm | 580 x 650 x 935mm | |
| Gross Weight | 57kg | 61kg | |

A = Electronic A-M = Mechanical Control *Options Available

| WATER-TEMPERATURE | 38°C | 70% | 65% | 60% | 55% | 50% |
|-------------------|------|------|------|------|------|------|
| | 32°C | 80% | 70% | 60% | 55% | 55% |
| | 25°C | 90% | 80% | 70% | 60% | 60% |
| | 15°C | 100% | 100% | 80% | 70% | 65% |
| | 10°C | 105% | 100% | 90% | 80% | 70% |
| | | 10°C | 21°C | 32°C | 38°C | 43°C |

AMBIENT-TEMPERATURE

DISTRIBUTED BY:





